



Electronic Products Design, Inc.

PO Box 1569 • 2554 Lake Wendell Road • Wendell, NC 27591

Phone (919) 365-9199 • Fax (919) 365-7005









Email: sales@epd-inc.com • Website: www.epd-inc.com

FILAMENT TX

DIMENSIONS

KVA	EPD NO	S1V	S1A	S2V	S2A	DUTY CYCLE	FREQ	PHASE	PRIMARY V	STYLE	WT(#)	H	W	D	MD	MW	NOTES
0.075	LT31089	6	10			CCS	60	1	120	4	8	4.5	3.75	3.1	2.5	3	
0.11	T21910	10.OCT	10			CCS	60	1	210/220/230/240	2	4	3.3	3	4	3	2.5	
0.213	LT31125	15.2	15			CCS	60	1	110/120	2	8	3.5	4.25	2.8	2.38	3.44	
0.225	LT31043	15CT	15			CCS	60	1	120	2							
0.3	LT31059	15	20			ICAS	60	1	120	2							
0.3	LT31139	5CT	60			CCS	60	1	120	2	8.5	4.5	4.5	4	3	3.75	
0.3	T21909	12.6CT	25			CCS	60	1	210/220/230/240	2							
0.3	LT31126	7.5CT	55			CCS	60	1	230/240	2	12						
0.3	LT31143	7.5CT	55			CCS	60	1	115/120	2	12	6	5.25	3.6	2.87	4.38	
0.3	LT31033	7.5CT	55			CCS	60	1	220/240	2							
0.3	LT31102	7.5CT	55			CCS	60	1	120/240	2	12	6	5.25	3.6	2.87	4.38	
0.3	LT31126	7.5CT	55			CCS	60	1	230/240	2	12	6	5.25	3.6	2.87	4.38	
0.3	LT31133	7CT	80			CCS	60	1	120/240	2	20	7	6	4.8	3.63	5.38	
0.3	LT31106	7.5CT	75			CCS	60	1	120/240	2	16						
0.3	LT31037	7CT	90			CCS	60	1	220	2							
0.3	LT31032	7.5CT	100			CCS	60	1	240	2	19	7.5	5.25	5.25	4.16	4.38	
0.3	LT31105	7.5CT	100			CCS	60	1	240+/-10	2	19						
0.3	LT31128	7.5CT	100			CCS	60	1	125/134	2	19	4.4	5.25	5.25	4.16	4.38	
0.3	LT31027	7.5CT	110			CCS	50/60	1	110/220	2	20	7	5.25	5.4	4.62	4.38	
0.3	LT31107	6.3CT	160			CCS	60	1	230/240/250	2	27	5.32	6.38	5.5	3.87	5.31	
0.3	LT31127	7.5CT	160	6.3CT		CCS	60	1	240	2	27	6.3	6.4	5.5	4.13	5.31	ONE Winding
0.3	LT31055	15	80			ICAS	60	1	120	2	19						
0.3	LT31066	15.4	150			ICAS	60	1	240	2	33	6.5	6.75	4.16	4.16	6.13	

ELECTRONIC PRODUCTS DESIGN, INC. STYLE SHEET

 <p>STYLE 1 HORIZONTAL CHANNEL</p>	 <p>STYLE 2 HORIZONTAL BRACKET</p>	 <p>STYLE 3 VERTICAL CHANNEL</p>
 <p>STYLE 4 VERTICAL BRACKET</p>	 <p>STYLE 5 SIMPLE TYPE</p>	 <p>STYLE 6 CORE TYPE</p>
 <p>STYLE 7 SHELL TYPE</p>	 <p>STYLE 8 THREE-PHASE</p>	



Electronic Products Design, Inc.

PO Box 1569 • 2554 Lake Wendell Road • Wendell, NC 27591

Phone (919) 365-9199 • Fax (919) 365-7005

Email: sales@epd-inc.com • Website: www.epd-inc.com

PLATE VOLTAGE

DIMENSIONS

KVA	EPD NO	S1 V	S1 A	S2 V	S2 A	DUTY CYCLE	FREQ	PHASE	PRIMARY V	STYLE	WT (#)	H	W	D	MD	MW	NOTES
0.281	LT31096	500	0.5		6.3 @5A	CCS	60	1	120	2	8	3.8	4.5	3.7	3.0	3.8	
0.6	LT31095	1200	0.5			CCS	60	1	120	2	15	5.3	5.3	4.5	3.6	4.4	
1.12	LT31094	1600	0.70			CCS	60	1	120	7	18	7.5	8.5	7.5	3.5	6.0	
1.65	LT31088	1650	1.00			ICAS	60	1	120	4	27	6.38	5.31	5.30	4.13	4.25	
2.2	LT31024	2200	1			CCS	60	1	120	7	56						
2.25	LT31145	4500CT	0.5			CCS	60	1	120	4							
2.34	LT31116	6320CT	0.35		365 @0.35A	CCS	60	1	115/230	4	55	9	7.5	5.5	4.75	5.87	COLLINS 30S-1M
2.75	LT31146	2200	1.25		2000	CCS	60	1	120/240	7							
2.8	LT31071	2800	1			ICAS	60	1	240 +/-10	7	43	8.5	9.0	8.0	4.0	5.5	
2.8	LT31076	2800	1			ICAS	60	1	200,220,240	7	43						
2.94	LT31100	2450	1.2			ICAS	60	1	120/240	7	13	8.5	9.0	8.3	4.0	6.5	
3	LT31064	1500	2			CCS	60	1	120/240	7	63	9.5	10.0	8.2	4.13	7.0	
3	LT31080	3000	1			CCS	60	1	240 +/-10	7	60	10.0	10.0	8.3	4.1	7.0	
3.1	LT31040	3100	1			CCS	60	1	120	7	60	9.5	10.0	8.1	6.0	7.0	
3.2	LT31132	1600	2			CCS	60	1	120/240	7	60	9.5	10	8.12	6	7	
3.45	LT31119	2300	1.5	1900	1600	ICAS	60	1	220/240	7	43	8.5	9	8	4	5.5	
3.75	LT31075	2500	1.5	2200		ICAS	60	1	240 +/-10	7	43	8.5	9.0	8.0	4.0	5.5	
3.8	LT31136	3500	1		10.2CT @30A	CCS	60	1	120/240	7	56	9	10	8.25	4.125	7	HENRY 2K-4-XM
4	LT31118	4000	1	2800	2100	CCS	60	1	230/240	4	80	10.5	8	9.25	6.25	7	
4.8	LT31058	3200	1.5			ICAS	60	1	220/240	7	82						
4.8	LT31138	3200	1.5			CCS	60	1	220/230/240	7	82	10.5	11	9	4.87	8	
5.4	LT31144	3600	1.5			ICAS	60	1	220/240	7	64	10	10	8.12	4.125	7	
6.00	LT31061	4000	1.5	3200		CCS	60	1	120/240	7	110	12.0	14.0	7.5	3.5	7.0	
7.5	LT31051	4500	1.5			CCS	60	1	235/245	7	110						
8.0	LT31087	4000	2.0	3400.0		CCS	60.0	1.0	240	7	110	12.0	12.0	7.5	5.8	7.0	
8	LT31117	4500	2	3500		CCS	60	1	220/230/240	7	121	12	12	7.5	5.75	7	
9.6	LT31086	4800	2.00	4400		ICAS	60	1	230/240/250	7	112	12.0	12.0	10.0	5.75	7.0	
9.6	LT31091	4800	2.00	3800	2800/2000	CCS	60	1	220/240	7	130	12.0	12.0	10.0	5.8	7.0	
12.6	LT31079	4200	3			ICAS	60	1	240	7	150						
13	LT31048	4000	3.25			CCS	60	1	220/240	7	145						
14	LT31078	7000	2		5000	CCS	60	1	240 +/-10	7	180	14.5	16.0	10.0	6.0	10.0	
15.8	LT31129	1500	10.5			CCS	60	1	460/480/500	7	188	14.2	16	10	6	10	
16	LT31142	4000	4		3500	CCS	60	1	240	7	190	16	14.5	10	6	10	
16.5	LT31065	5500	3			CCS	60	1	240	7	260	16.0	20.0	10.0	6.0	14.0	
17.5	LT31025	5000	3.5			CCS	60	1	220/240	7	250						
20	LT31101	5000	4	4800	3800/2800	CCS	60	1	220/240	7	280	15.5	18.0	12.0	6.0	12.0	
20.8	LT31149	5200	4	2000		CCS	60	1	220/240	7	230	18	15.5	12	6	12	
22	LT31070	6800 CT	3.23			CCS	60	1	240/480	7	280	16.5	18.0	12.0	6.0	12.0	
25	LT31099	5000	5	4200		CCS	60	1	240	7	320	16.5	21.0	14.0	6.0	15.0	
25	LT31112	5000	5			CCS	60	1	240	7	320	16.0	21.0	14.0	6.0	15.0	
30	LT31074	6000	5	5000		CCS	60	1	240 +/-10	7	360	18.3	21.0	12.5	6.0	15.0	
32.5	LT31098	6500	5			CCS	60	1	220/240	7	420						
32.5	LT31140	6500	5	5500	5000	CCS	60	1	230/240/250	7	360	18	21	13	6	15	
39	LT31154	6500	6	5200	3000	CCS	60	1	220/240	7	410	18	21	14	7	15	
45.6	LT31093	7600	6	6000	6000	CCS	60	1	240	7	440	18.0	21.0	14.0	7.0	15.0	